

C15-500



☀️ 15 inch ☀️ 500 Watts
☀️ 99 dB ☀️ 43 ~ 3000 Hz



KEY FEATURES:

- ① 1000 W continuous program power capacity
- ② Sensitivity: 99dB 1w/1m
- ③ 76mm(3") high temperature inside/outside voice coil with copper clad aluminum wire
- ④ Vented back plate increases airflow to provide enhanced cooling
- ⑤ Treated cone for water protection
- ⑥ Increased power handling and more mid-high over C15-400
- ⑦ Ideal for compact 2 or 3-way systems

GENERAL SPECIFICATIONS



Nominal Diameter	380mm /15inch
Rated Impedance	8 ohm
Nominal Power handling ¹	500 Watts
Program Power ²	1000 Watts
Sensitivity(1w/1m) ³	99 dB
Frequency Range ⁴	43 ~ 3000Hz
Minimum Impedance(Zmin)	6.6 ohm
Voice Coil Diameter	76mm /3inch
Voice Coil Material	CCAW
Former Material	Glass Fiber
Voice Coil Winding Depth	19 mm
Number of layers	2(inside/outside)
Magnet gap depth	10.5 mm
Basket	Cast Aluminum
Flux Density	1.2 T
Magnet Out Diameter/Wgt	200mm / 100 oz

THIELE - SMALL PARAMETERS⁵

Resonance frequency	Fs	46 Hz
DC resistance	Re	5.3 ohm
Mechanical factor	Qms	12.3
Electrical factor	Qes	0.39
Total factor	Qts	0.38
Mechanical compliance	Cms	0.12 mm/N
Mechanical resistance of total-driver losses	Rms	1.45 kg/s
Effective Moving Mass	Mms	98 g
Half-space efficiency	Eff	3.1%
BL Factor	BL	20.2 T.m
Equivalent Cas air load	Vas	125 liters
Effective piston area	Sd	0.0855 m ²
Max. linear excursion ⁶	Xmax	±7 mm
Max. excursion before damage	Xdam	±17.7mm
Voice coil inductance(1kHz)	Le	0.87 mH
Efficiency Bandwidth Product	EBP	118

MOUNTING INFORMATION

Overall Diameter	393 mm
Bolt Circle Diameter	375 mm
Bolt Hole Diameter	6.5 mm
Baffle Cutout Diameter	355 mm
Overall Depth	169 mm
Air volume occupied by driver	5.8 liters
Net Weight	8.7 kg
Shipping Weight	9.8 kg
Shipping Box	430x430x205 mm



NOTES:

- AES standard
- Program Power is defined as 3 dB greater than the nominal power handling.
- Sensitivity is measured at 1W input on rated impedance at 1m on axis.
- Frequency range is defined as the band of frequencies delineated by the lower and upper limits where the output level drops by 10dB below the rated sensitivity.
- Thiele-Small parameters are measured with Klippel DALPM module BEFORE preconditioning test.
- The maximum linear excursion is calculated as: $(Hvc-Hg)/2 + Hg/4$ where Hvc is the voice coil depth and Hg is the gap depth.
- Vb: Net internal volume of box after subtracting the volume of internal objects.